



Anderson LST-X Utility Series

[Read More](#)

SKU: A-LST-X-US

Categories: [Anderson Manufacturing](#)

Product Description

Anderson LST-X Utility Series

- G.V.W.R. : 7,000#
 - G.A.W.R. : Each Axle - 3,500#
 - Coupler: 2" Adjustable Bolt-On
 - Safety Chain: 8/0 Grade 30 w/ Hooks
 - Jack: 2K Top-Wind Pole
 - Tongue: 4x3x1/4" Angle
 - Frame: 3x2x3/16" Angle (3x4x1/4" Angle 18'+)
 - Crossmembers: 3x2x3/16" Angle w/ 24" Centers
 - Top Rails: 2x3" 11 Ga. Tube
 - Uprights: 2x2x1/8" Angle w/ Spare Mount
 - Fenders: 9x72" - Diamond Plate w/ Steel Backs
 - Bumper: 2x4" 14 Ga. CNC Laser Tubed w/ Concealed Tag Mount & Integrated EZ-Shock Gate Assist
 - Axle: (2) 3,500# Cambered Electric Brake
 - Suspension: Multi-Leaf Spring w/ Equalizer
 - Tires: ST205/75R15 Load Range C
 - Wheel: 15" 5-Bolt White Spoke (5 on 4.5 Pattern)
 - Deck: 2" Pressure Treated Pine
 - Lights: L.E.D. Stop, Tail, & Turn
 - Vehicle Plug: 7- Way RV w/ Breakaway & SnapNSeal
 - Paint Prep: 5 - Stage Super Blast Treatment
 - Paint: Super Durable Powdercoat
 - Gate: 4' HD-X Rental Style w/ Angle Runners
 - Gate Lock: CNC Machined Lockable Pin Latch
 - Dimensions: 1,340# - 10', 1,430# - 12', 1,520# - 14', 1,610# - 16', 1,700# - 18', 1,790# - 20', 1,880# - 22'
-