



Anderson 15T Commercial Tilt Series

[Read More](#)

SKU: A-15T-C-TS

Categories: [Anderson Manufacturing](#)

Product Description

Anderson 15T Commercial Tilt Series

- G.V.W.R. : 32,500#
 - G.A.W.R. : Each Axle - 15,000#
 - Coupler: 2-5/16" - Adjustable (Gooseneck/Pintle)
 - Safety Chain: 7/16" Grade 70 w/ Hooks
 - Jack: Bolt-On 25K 2-Speed Landing Gear
 - Frame: 14" Structural I-Beam
 - Tilt Deck: Custom Fabricated Beam w/ Lock
 - Crossmembers: 4" Channel w/ 16" Centers
 - Side Rails: 8" Channel w/ (10 Total) D-Rings
 - Ramps: Beveled Approach Plate w/ Recessed Lights & Tube Bumper
 - Axle: (2) 15,000# Oil-Bath Electric Brake
 - Suspension: HD Hutch 9700-Style
 - Tires: ST215/75R17.5 Load Range H
 - Wheel: Dually 17.5" 8-Bolt Grey (8 on 275mm Pa.)
 - Deck: 2" Rough Cut Oak
 - Lights: L.E.D. Stop, Tail, & Turn
 - Vehicle Plug: 7 - Way RV w/ Breakaway & SnapNSeal
 - Paint Prep: 3- Stage Clean-Up & Prime Coat
 - Paint: Durable High Solids Acrylic Enamel
 - Dimensions: 7,000# - 25', 7,250# - 29'
 - Standard Features: 5' Low Angle Dovetail, Cushioning Tilt Cylinder, Lockable Neck/Tongue Mounted Toolbox, Full-Length Diamond Plate Drive-Over Fenders, Lever Unlock/Self-Locking Tilt Deck Latch
-