



IronCraft 2510 Series: 10' Flex-Wing Rotary Cutter 540 RPM 4 USED AIRCRAFT TIRES

Price: \$17,026 Our Price: \$15,149

[Read More](#)

SKU: 2510-IC-4AT

Categories: [Ironcraft](#)

Product Description

IronCraft 2510 Series: 10' Flex-Wing Rotary Cutter 540 RPM 4 USED AIRCRAFT TIRES

The **IronCraft 2510 Flex-Wing Cutter** is engineered to deliver high-performance results with surprisingly low horsepower requirements. Ideal for landowners managing tough terrain, this **123" working width cutter** combines a high-speed gearbox with heavy-duty construction.

Design efficiency is at the forefront of the 2510 series, featuring a **flat-top deck** for easy cleaning and a narrow 96.5" transport width for effortless mobility between jobsites. Whether you are clearing brush up to 2" in diameter or maintaining expansive pastures, this flex-wing cutter provides the reliability you expect from IronCraft.

Core Performance Features

- **Low HP Requirement:** Operates efficiently with only 25-60 PTO horsepower.
- **Flexible Maneuverability:** Wing flex ranges from 20° down to 85° up for uneven landscapes.
- **Superior Cutting Protection:** Equipped with round stump jumpers and a 175 HP-rated main gearbox.
- **Low Maintenance:** Features an 11-gauge flat top deck and replaceable skid shoes.

Detailed Technical Specifications

- **Working Width:** 123" (10' Dual Spindle Flex-Wing)
- **Cutting Capacity:** Clears brush up to 2" diameter
- **Cutting Height:** Adjustable from 1-3/4" to 11-1/2"
- **Transport Width:** 96.5" for easy gate and road access
- **Deck Height:** 11" with 7-gauge side bands

Drivetrain & Hardware

- **Gearbox Rating:** 175 HP (Center) / 75 HP (Outboard)
- **PTO Drive Shaft:** ASAE CAT 5 (Main) / ASAE CAT 4 (Wing)
- **Driveline Protection:** Slip Clutch standard

- **Blade System:** 1/2" x 3" Uplift blades with 5-1/4" overlap
- **Tire Type:** Four 20" Laminated tires for maximum stability

Standard Safety & Warranty

- **Gearbox Warranty:** 5-Year Limited Warranty
 - **Guarding:** Single row chains included as standard
 - **Hitch:** Swivel pivot self-leveling hitch for smooth towing
 - **Safety:** Standard safety tow chain included
-