



IronCraft 2515 Series: 15' Medium-Duty Flex-Wing Rotary Cutter 540 RPM WITH 6-26" LAMINATED TIRES

Price: \$21,944 Our Price: \$19,826

[Read More](#)

SKU: 2515-IC-LL6

Categories: [Ironcraft](#)

Product Description

IronCraft 2515 Series: 15' Medium-Duty Flex-Wing Rotary Cutter 540 RPM WITH 6-26" LAMINATED TIRES

The **IronCraft 2515 Series** is the ultimate solution for large-scale land management, offering a massive **180" cutting width** designed for efficiency. Engineered for tractors with a **50 minimum PTO horsepower**, this medium-duty flex-wing cutter handles tough vegetation, weeds, and brush up to 2.5" in diameter with ease. Built with a **smooth-top deck** for minimal debris buildup and a heavy-duty spring suspension for smooth tracking over uneven terrain, the 2515 is as easy to maintain as it is to operate. With a narrow **90" transport width**, moving this high-capacity cutter between fields is simple and safe.

Performance & Durability Features

- **Triple Spindle System:** Features three spindles with two free-swinging blades each to absorb impact shock.
- **Heavy-Duty Gearboxes:** Rated at 235 HP (Center) and 190 HP (Outboard) for maximum torque and longevity.
- **Superior Protection:** Equipped with slip clutches to protect the driveline and ASAE CAT 6 main PTO shaft.
- **Flexible Contour Tracking:** Wings flex from 22° down to 88° up, allowing for perfect cuts on ditch banks and rolling hills.

Detailed Technical Specifications

- **Working Width:** 180" (15 Feet)
- **Cutting Capacity:** Clears brush and saplings up to 2.5" diameter
- **Cutting Height:** Adjustable from 2" to 15" via hydraulic cylinder
- **Deck Thickness:** Rugged 10-gauge steel construction
- **Side Bands:** 1/4" x 13-1/2" for enhanced structural rigidity

Drivetrain & Build Quality

- **PTO Speed:** Available in 540 or 1000 RPM configurations
- **Blade System:** 1/2" x 4" uplift blades with a 6" overlap and round pan blade holders
- **Suspension:** Single heavy-duty spring system
- **Wheels:** Includes six 26" laminated tires for superior flotation and stability
- **Hitch:** Swivel pivot self-leveling hitch for smooth towing

Standard Safety & Reliability

- **Warranty:** 5-Year Limited Gearbox Warranty
 - **Guarding:** Single row discharge chains, driveline shields, and clutch shields included standard
 - **Transport Safety:** Standard safety tow chain and 90" narrow transport width
 - **Maintenance:** Replaceable skid shoes and easy-clean flat deck design
-