



IronCraft 300 Series: 6' Medium-Duty Smooth-Top Cutters Dual Tailwheels SLIP CLUTCH W/RUBBER BELTING

Price: \$3,703 Our Price: \$3,366

[Read More](#)

SKU: 3062TSCB

Categories: [Ironcraft](#)

Product Description

IronCraft 306 2 TW: 6' Smooth-Top Rotary Cutter with Dual Tailwheels SLIP CLUTCH W/RUBBER BELTING

The **IronCraft 306 2 TW** is a high-performance 72" rotary cutter designed for tractors ranging from **47 to 90 PTO horsepower**. This medium-to-heavy-duty cutter is the ideal solution for clearing dense weeds, thick grass, and **brush up to 2" in diameter**.

What sets this model apart is its **dual tailwheel configuration**, providing superior stability and a more consistent cut on uneven terrain. The **smooth-top deck design** prevents water and organic material from collecting on top, significantly extending the life of the machine by reducing rust and corrosion.

Key Performance & Safety Benefits

- **Enhanced Stability:** Dual 15" laminated tailwheels ensure better weight distribution and floatation.
- **Shock-Absorbing Blades:** Two free-swinging 1/2" x 3" blades reduce the impact shock on the gearbox when hitting rocks or stumps.
- **Durable Construction:** Built with a 10-gauge steel deck and heavy-duty 8-1/2" side bands.
- **Driveline Protection:** Features a Series 4 PTO shaft with a standard slip clutch to prevent mechanical failure.

Technical Specifications (Model 306 2 TW)

- **Working Width:** 72" (6 Feet)
- **Cutting Capacity:** Up to 2" diameter material
- **HP Requirement:** 47 - 90 PTO HP
- **Blade Tip Speed:** 14,500 FPM (Feet Per Minute)
- **Gearbox Rating:** 100 HP High-Torque Gearbox

Build Quality & Maintenance

- **Blade Holder:** Heavy-duty 1/2" steel plate for maximum rigidity.
- **Hitch Compatibility:** Category 1 (Cat 1) 3-point hitch.

- **Tailwheel Type:** Two 15" Laminated tires with greaseable hubs for easy upkeep.
- **Skid Shoes:** Replaceable skid shoes to protect the cutter frame.
- **PTO Speed:** Standard 540 RPM.

Warranty & Safety Options

- **Gearbox Warranty:** 5-Year Limited Manufacturer Warranty.
 - **Standard Shielding:** Includes driveline and clutch shields for operator safety.
 - **Discharge Protection:** Optional rubber guards or safety chains available for front and rear.
-