



IronCraft 3515 Series: 15' Heavy-Duty Flex-Wing Rotary Cutter 21 SPLINE 1 3/8\" 1000 RPM 4-27\" AIRCRAFT TIRES

Price: \$24,782 Our Price: \$22,389

[Read More](#)

SKU: 3515-IC-LAT4-21-1000

Categories: [Ironcraft](#)

Product Description

IronCraft 3515 Series: 15' Heavy-Duty Flex-Wing Rotary Cutter 21 SPLINE 1 3/8\" 1000 RPM 4-27\" AIRCRAFT TIRES

The **IronCraft 3515** is engineered for the most demanding land management projects, providing a massive **180\" working width** and unmatched structural integrity. Designed for tractors with a **60 minimum PTO horsepower**, this heavy-duty cutter is built to handle thick brush and saplings up to **3.5\" in diameter**.

The 3515 Series stands out with its reinforced deck structure and 1/4\" wall tubing along the hinges for superior protection. Exclusive **standard deck rings** are included on every deck to prevent damage from bent blades, while the wing-fold hydraulic system is integrated into the center deck weldment for maximum strength.

Advanced Engineering & Cut Quality

- **Precision Blade Pans:** Heavy 7-gauge press-formed blade pans feature a specialized design to reduce the "ripple effect," ensuring superior rotational balance and gearbox longevity.
- **Maximum Structural Integrity:** Reinforced center deck weldment and heavy-duty 1/4\" x 13-1/2\" side bands provide a rigid frame for tough terrain.
- **High-Capacity Drivetrain:** Equipped with a 235 HP center gearbox and 190 HP outboard gearboxes to handle high-torque loads.
- **Extreme Wing Flex:** Features a wing range of 22° down to 100° up, making it ideal for steep embankments and ditch clearing.

Technical Specifications

- **Cutting Capacity:** Material up to 3-1/2\" diameter
- **Working Width:** 180\" (15 Feet)
- **Transport Width:** 90\" for safe road travel
- **Cutting Height:** Adjustable from 2\" to 15\"
- **Weight:** 5,600 lbs with six 26\" laminated tires

Drivetrain & Build Hardware

- **PTO Speed:** 540 or 1000 RPM units available
- **Driveline Protection:** ASAE CAT 6 main PTO with slip clutch protection
- **Suspension:** Dual heavy-duty springs on the center tailwheel axle for smooth operation
- **Blade System:** 1/2" x 4" uplift blades with a 6" overlap for a clean, consistent cut
- **Hitch:** Swivel pivot self-leveling hitch for improved towing stability

Safety & Warranty Information

- **Gearbox Warranty:** 5-Year Limited Warranty
 - **Deck Rings:** Included as standard equipment to protect the mower deck
 - **Standard Guarding:** Single row safety chains and safety tow chain included
 - **Maintenance:** Replaceable skid shoes for easy serviceability
-