



IronCraft 3520 Series: 20' Heavy-Duty Flex-Wing Rotary Cutter 8-26" LAMINATED TIRES W/ LIGHT KIT - 540 RPM LIGHT KITS STANDARD, OPTIONAL WALKING TANDAM AXLES

Price: \$37,521 Our Price: \$33,581

[Read More](#)

SKU: 3520-LL8

Categories: [Ironcraft](#)

Product Description

IronCraft 3520 Series: 20' Heavy-Duty Flex-Wing Rotary Cutter 8-26" LAMINATED TIRES W/ LIGHT KIT - 540 RPM LIGHT KITS STANDARD, OPTIONAL WALKING TANDAM AXLES

Dominate wide-open spaces with the **IronCraft 3520 Flex-Wing Cutter**, the ultimate 240" clearing solution for utility right-of-ways, airports, and expansive agricultural fields. Engineered for tractors with at least **80 PTO horsepower**, this powerhouse is built to withstand the most punishing conditions while delivering a clean, reliable cut.

The 3520 is designed for maximum productivity and minimal downtime. With a **4" cutting capacity** and a massive 20-foot working width, it features a clean, flat-top deck design to prevent debris accumulation. Whether you are maintaining a trail system or clearing heavy brush, the 3520 is the heavy-duty sidekick your fleet needs.

Superior Stability & Cut Quality

- **Spring-Loaded Suspension:** Dual heavy-duty springs in the center and independent wing springs ensure a level cut on uneven terrain.
- **Heavy-Duty Components:** Equipped with large 1" internal leveling rods and 4" wide uplift blades for long-term durability.
- **Precision Engineering:** Standard deck rings protect the structure from blade impact, while round pan blade holders enhance rotational balance.
- **High-Performance Gearboxes:** Features a massive 275 HP main gearbox and 225 HP outboard gearboxes.

Technical Specifications

- **Working Width:** 240" (20 Feet)
- **Cutting Capacity:** Material up to 4" diameter
- **Transport Width:** 94" (standard) to 108" (with tandems)
- **Cutting Height:** Adjustable from 2" to 15"
- **Total Weight:** 8,700 lbs with 8-tire configuration

Drivetrain & Build Quality

- **PTO Speed:** Available in 540 RPM (16,600 FPM) or 1000 RPM (17,400 FPM)
- **Drive Shafts:** ASAE CAT 6 main and wing drive PTOs for maximum power transfer
- **Deck Strength:** 10-gauge center deck with ultra-tough 7-gauge wing decks
- **Side Bands:** 1/4" x 13-1/2" reinforced steel
- **Tire Options:** 20" or 26" Laminated, or 27" Foam Filled/Pneumatic

Warranty & Safety Standards

- **Gearbox Warranty:** Industry-leading 5-Year Limited Warranty
 - **Standard Safety:** Single row discharge chains and safety tow chain included
 - **Hitch Type:** Swivel pivot self-leveling hitch for smooth, safe towing
 - **Maintenance:** Replaceable skid shoes and easy-access grease points
-