



IronCraft 3700 Series: 7' Heavy-Duty Dual Edge Grader

Price: \$2,736 Our Price: \$2,458

[Read More](#)

SKU: 3707

Categories: [Ironcraft](#)

Product Description

IronCraft 3700 Series: 7' Heavy-Duty Dual Edge Grader

The **IronCraft 3707** is a premier **84" Dual Edge Grader**, also known as a land plane, engineered for high-efficiency grading and leveling. Designed for tractors between **40 and 80 horsepower**, this heavy-duty tool is the ultimate solution for maintaining gravel driveways, smoothing horse arenas, leveling garden plots, and grooming barn floors.

Built for maximum versatility, the 3700 Series features an **adjustable cutting depth** and a dual-blade system that eliminates the "washboard" effect common with single-blade scrapers. Whether you are a professional landscaper or a rancher, this grader is **Category 1 and 2 Quick Hitch compatible**, ensuring it integrates seamlessly into your existing fleet.

Superior Grading & Leveling Features

- **Dual Reversible Blades:** Two cutting edges work in tandem to move material forward and level high spots in a single pass.
- **Adjustable Scarifier Shanks:** Includes 6 heat-treated shanks with hardened tips, featuring three depth positions (at grade, 1-1/2" below, and 3" below) to rip compacted soil.
- **Replaceable Skid Shoes:** Large 3/16" thick skid shoes protect the side panels and ensure a consistent depth across the entire working width.
- **Heavy-Duty Frame:** Constructed with a 3/8" A-frame and 4" x 4" support tubes to handle the stress of 80 HP tractor applications.

Technical Specifications (Model 3707)

- **Working Width:** 84" (7 Feet)
- **Horsepower Requirement:** 40 - 80 HP
- **Weight:** 700 lbs for superior ground engagement and stability
- **Hitch Compatibility:** Category 1 & 2 (Quick Hitch Ready)
- **Shank Configuration:** 6 Adjustable, heat-treated scarifiers

Industrial Build Quality

- **Dual Rear Beams:** Two 3" x 3" beams spaced 21-1/8" apart for maximum structural rigidity.

- **Side Panel Dimensions:** 15-11/16" height and 52-3/8" length for high-volume material containment.
- **Hitch Type:** Secure clevis-type hitch for reduced wear on tractor pins.
- **Overall Footprint:** 89-5/8" width and 58-1/2" length.

Primary Applications

- **Gravel Driveway Maintenance:** Restore private roads and driveways by pulling material from the shoulders back to the center.
 - **Equestrian Arenas:** Level and groom horse arenas to ensure a safe, consistent footing for riders.
 - **Garden & Plot Prep:** Effortlessly smooth out tilled soil for large-scale planting or sod installation.
 - **Barn Floors & Feedlots:** Maintain level dirt or gravel surfaces in high-traffic livestock areas.
-