



IronCraft 3700 Series: 8' Heavy-Duty Dual Edge Grader

Price: **\$2,985** Our Price: **\$2,675**

[Read More](#)

SKU: 3708

Categories: [Ironcraft](#)

Product Description

IronCraft 3700 Series: 8' Heavy-Duty Dual Edge Grader

The **IronCraft 3708** is a high-capacity **8' Dual Edge Grader** (also known as a land plane) designed for tractors with **50 to 80 horsepower**. This professional-grade attachment is the ultimate solution for maintaining expansive gravel driveways, smoothing horse arenas, and leveling large garden plots or barn floors with unmatched efficiency.

Engineered with a dual-blade system, the 3700 series eliminates the "washboard" effect common with standard blades, filling in low spots while cutting down high points simultaneously. This model is **Category 1 and 2 Quick Hitch compatible**, making it a versatile powerhouse for any heavy-duty fleet.

Key Performance & Leveling Features

- **Dual Reversible Blades:** Features two high-carbon steel cutting edges that work in tandem to create a perfectly level surface in fewer passes.
- **Adjustable Scarifier Shanks:** Includes 6 heat-treated shanks with hardened tips that can be adjusted to grade level, 1-1/2", or 3" below grade for aggressive ripping.
- **Smooth Finishing Action:** The adjustable blade height and cutting depth allow for fine-tuned control over the finish of your dirt or gravel surfaces.
- **Replaceable Skid Shoes:** Equipped with durable 3/16" skid shoes to protect the side panels and ensure consistent depth control.

Technical Specifications (Model 3708)

- **Working Width:** 96" (8 Feet)
- **Horsepower Requirement:** 50 - 80 HP
- **Hitch Type:** Clevis Type (Cat 1 & 2 Compatible)
- **Total Weight:** 740 lbs for superior ground engagement
- **Scarifier Count:** 6 Adjustable Position Shanks

Rugged Construction & Build Quality

- **Heavy-Duty Frame:** Built with a 3/8" A-frame and a 4" x 4" x 1/4" scarifier support tube for industrial longevity.

- **Reinforced Side Panels:** 15-11/16" tall side panels with a length of over 52" to contain and distribute large volumes of material.
- **Rear Beam Stability:** Features two 3" x 3" beams spaced 21-1/8" apart to maintain structural rigidity under high-torque loads.
- **Overall Dimensions:** 101-5/8" width and 58-1/2" length.

Professional & Agricultural Applications

- **Road & Driveway Maintenance:** Restore long gravel roads and private drives by redistributing aggregate perfectly.
 - **Equestrian Arenas:** Maintain consistent, level footing for horse arenas and training facilities.
 - **Site Preparation:** Level topsoil and clear debris for large-scale landscaping or construction prep.
 - **Barn & Feedlot Management:** Smooth out high-traffic dirt floors and livestock areas for better drainage and accessibility.
-