



IronCraft T624: 24' Six-Basket Hay Tedder with Hydraulic Leveling

Price: ~~\$17,094~~ Our Price: \$15,333

[Read More](#)

SKU: T624-H-IC

Categories: [Ironcraft](#)

Product Description

IronCraft T624: 24' Six-Basket Hay Tedder with Hydraulic Leveling

The **IronCraft T624** is a professional-grade **24-foot Six-Basket Hay Tedder**, engineered for high-output operations using tractors between **50 and 60 PTO horsepower**. This massive 24' implement is designed to cover vast acreage in record time, ensuring your forage is fluffed, spread, and dried uniformly to lock in peak nutritional value.

Equipped with **hydraulic wing folding** and **hydraulic working angle adjustment**, the T624 allows for total control from the tractor cab. Its standout feature is the **walking tandem wheel system**, which provides unparalleled stability and ground following on uneven terrain, preventing tine damage and soil contamination.

High-Capacity Precision & Forage Features

- **Expansive 24' Working Width:** Maximize your field efficiency by covering more ground in every pass, perfect for beating tight weather windows.
- **Six-Rotor Distribution System:** Six independent rotors work in sync to lift and distribute heavy windrows, ensuring even air circulation and rapid dry-down.
- **Walking Tandem Axles:** Features 8 flotation tires (16 x 6.5-8) in a walking tandem configuration to glide over ruts and ridges for the smoothest possible operation.
- **Hydraulic Leveling:** Adjust the pitch of the rotors on the fly to match crop conditions without leaving the operator's seat.

Technical Specifications (Model T624)

- **Working Width:** 24 Feet
- **Horsepower Requirement:** 50 - 60 PTO HP
- **Rotor Configuration:** 6 Baskets with High-Strength Tines
- **Transport Dimensions:** 9.8' Transport Width x 12.1' Transport Height
- **Operating Weight:** 1,740 lbs for industrial durability
- **Safety:** Road Signaling Kit included as standard equipment
- **Hydraulic Requirements:** 2 Rear Remotes Required

Industrial Build Quality & Design

- **Heavy-Duty Pull-Type Hitch:** Designed for stable tracking behind utility tractors at high field speeds.
- **Articulated Frame Sections:** Allows the 24-foot frame to flex and follow complex field contours effortlessly.
- **Hydraulic Wing Fold:** Folds to a compact 9.8' width for safe travel through gates and on public roads.
- **Premium Road Signaling:** Standard lighting kit ensures visibility during transport between far-flung fields.

Primary Commercial Haying Applications

- **Large-Scale Forage Operations:** The 24-foot reach is a game-changer for commercial alfalfa, grass, and cereal grain hay producers.
 - **High-Speed Curing:** Engineered for contractors who need to process massive volumes of hay per hour while maintaining perfect forage quality.
 - **Variable Terrain Harvesting:** The walking tandem wheels make this the best choice for rough, terraced, or undulating hay fields.
 - **Professional Crop Management:** Achieve perfectly consistent moisture levels across the entire field for safer, more efficient baling.
-