



IronCraft UH Series: 60" Heavy-Duty Reverse Rotation Gear Drive Tiller

Price: **\$3,888** Our Price: **\$3,590**

[Read More](#)

SKU: UH-60-R

Categories: [Ironcraft](#)

Product Description

IronCraft UH Series: 60" Heavy-Duty Reverse Rotation Gear Drive Tiller

The **IronCraft UH-60-R** is an industrial-grade **60-inch Heavy-Duty Rotary Tiller** engineered for tractors between **40 and 55 horsepower**. Built to dominate demanding landscapes, this reverse-rotation tiller is specifically designed to cut through stony, compacted, and virgin soils that stall standard forward-rotation models.

Featuring a high-performance **gear-drive system** and **Category 1 and 2 compatibility**, the UH-60-R offers professional-level durability. The reverse-rotation action pulls the tiller into the ground, preventing "walking" on hard surfaces and ensuring a deep, pulverized seedbed in a single pass.

Industrial Performance & Reverse Tillage Benefits

- **Aggressive Reverse Rotation:** The counter-rotating tines pull the implement into the soil, burying large clods and stones at the bottom of the furrow for a superior surface finish.
- **High-Torque Gear Drive:** Unlike chain-driven models, the oil-bath gear drive system provides maximum power transfer and long-term reliability in extreme conditions.
- **Deep Ground Penetration:** Capable of reaching a maximum working depth of 7-1/2", ideal for deep-root crops and extensive soil renovation.
- **42-Tine Configuration:** Features 7 flanges with 6 tines per flange, ensuring intensive soil pulverization and thorough aeration.

Technical Specifications (Model UH-60-R)

- **Working Width:** 65" (Approx. 5.5 Feet)
- **Horsepower Requirement:** 40 - 55 PTO HP
- **Hitch Type:** Category 1 & 2 (Cat 1 & 2)
- **Operating Weight:** 860 lbs for maximum down-pressure and stability
- **Rotor Diameter:** Heavy-duty 3-1/2" rotor with 19" swing diameter

Rugged Construction & Design

- **Stony Soil Capability:** Engineered specifically to handle ground with high rock content without excessive wear.

- **Heavy-Duty Build:** At 860 lbs, this tiller stays in the ground rather than bouncing on top of hardpan.
- **Standard PTO Speed:** Optimized for 540 RPM operation for peak efficiency.
- **Dual Hitch Compatibility:** Fits both Category 1 and Category 2 three-point hitches.

Professional & Agricultural Applications

- **Commercial Site Preparation:** Perfect for leveling construction sites and breaking up sun-baked clay.
 - **New Field Establishment:** Ideal for breaking sod and turning virgin land into productive garden or farm acreage.
 - **Stony Ground Management:** The reverse rotation helps "screen" stones by burying them under a layer of fine topsoil.
 - **Landscape Renovation:** Quickly restores neglected or compacted properties to a plantable state.
-